

Niax* Silicone L-6620 Urethane Additives - Rigid Foam

Product Description

Niax Silicone L-6620 is a silicone copolymer that may be considered for use in the manufacture of rigid polyurethane and polyisocyanurate foams. It can deliver increased nucleation and emulsification helping to provide better foam stability control and finer cells formation.

Key Features and Typical Benefits

- Niax Silicone L-6620 can be considered for foams obtained by continuous and discontinuous process blown with hydrocarbon or mixture of hydrocarbon and fluorinated blowing agents.
- Niax Silicone L-6620 can be used as main or as co-surfactant to improve the emulsification of blowing agents, especially hydrocarbons, and to reduce foam defects linked to an insufficient emulsification power, especially in foam produced by continuous lamination and at high levels of blowing agents.
- Niax Silicone L-6620 can have a strong nucleation power that can help to promote regular and very fine cells texture with improved insulation properties.
- Niax Silicone L-6620 can also improve compatibility of polyol and MDI extending the processability windows using high and medium pressure mixing devices.
- The common usage range for Niax Silicone L-6620 is 2.0 to 3.0 parts per hundred of polyol (php).

Typical Physical Properties

Appearance	Clear, liquid
Viscosity at 25 °C, cSt	750
Specific Gravity at 25 °C	1.05
Freezing Point, °C	< -10

Typical properties are average data and are not to be used as or to develop specifications.

Patent Status

Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute the permission, inducement or recommendation to practice any invention covered by any patent, without authority from the owner of the patent.

Product Safety, Handling and Storage

Customers should review the latest Safety Data Sheet (SDS) and label for product safety information, safe handling instructions, personal protective equipment if necessary, emergency service contact information, and any special storage conditions required for safety. Momentive Performance Materials (MPM) maintains an around-the-clock emergency service for its products. SDS are available at www.momentive.com or, upon request, from any MPM representative. For product storage and handling procedures to maintain the product quality within our stated specifications, please review Certificates of Analysis, which are available in the Order Center. Use of other materials in conjunction with MPM products (for example, primers) may require additional precautions. Please review and follow the safety information provided by the manufacturer of such other materials.

Limitations

Customers must evaluate Momentive Performance Materials products and make their own determination as to fitness of use in their particular applications.

Contact Information

Email 4information@momentive.com

Telephone North America

+1 800 295 2392 +1 614 986 2495

Latin America +5511 4534 9650 Europe, Middle East, Africa and India +00 800 4321 1000 +40 212 534754 Asia Pacific China +800 820 0202 Japan +81 276 20 6182 All Other Countries +60 3 9206 1543

For literature and technical assistance, visit our website at: www.momentive.com

DISCLAIMER:

THE MATERIALS, PRODUCTS AND SERVICES OF MOMENTIVE PERFORMANCE MATERIALS INC. AND ITS SUBSIDIARIES AND AFFILIATES (COLLECTIVELY "SUPPLIER"), ARE SOLD SUBJECT TO SUPPLIER'S STANDARD CONDITIONS OF SALE, WHICH ARE INCLUDED IN THE APPLICABLE DISTRIBUTOR OR OTHER SALES AGREEMENT, PRINTED ON THE BACK OF ORDER ACKNOWLEDGMENTS AND INVOICES, AND AVAILABLE UPON REQUEST. ALTHOUGH ANY INFORMATION, RECOMMENDATIONS, OR ADVICE CONTAINED HEREIN IS GIVEN IN GOOD FAITH, SUPPLIER MAKES NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, (i) THAT THE RESULTS DESCRIBED HEREIN WILL BE OBTAINED UNDER END-USE CONDITIONS, OR (iii) AS TO THE EFFECTIVENESS OR SAFETY OF ANY DESIGN INCORPORATING ITS PRODUCTS, MATERIALS, SERVICES, RECOMMENDATIONS OR ADVICE. EXCEPT AS PROVIDED IN SUPPLIER'S STANDARD CONDITIONS OF SALE, SUPPLIER AND ITS REPRESENTATIVES SHALL IN NO EVENT BE RESPONSIBLE FOR ANY LOSS RESULTING FROM ANY USE OF ITS MATERIALS, PRODUCTS OR SERVICES DESCRIBED HEREIN. Each user bears full responsibility for making its own determination as to the suitability of Supplier's materials, services, recommendations, or advice for its own particular use. Each user must identify and perform all tests and analyses necessary to assure that its finished parts incorporating Supplier's products, materials, or services will be safe and suitable for use under end-use conditions. Nothing in this or any other document, nor any oral recommendation or advice, shall be deemed to alter, vary, supersede, or waive any provision of Supplier's standard Conditions of Sale or this Disclaimer, unless any such modification is specifically agreed to in a writing signed by Supplier. No statement contained herein concerning a possible or suggested use of any material, product, service or design is intended, or should be construed, to grant any license under any patent or other intellectual property right of Supplier covering such use or design, or as a recommendation for the use of such material, product, service or design in the infringement of any patent or other intellectual property right.

*Niax is a trademark of Momentive Performance Materials Inc.

Momentive and the Momentive logo are trademarks of Momentive Performance Materials Inc.



260 Hudson River Road Waterford, NY 12188 USA momentive.com

Copyright 2016 Momentive Performance Materials Inc. All rights reserved.